

Trade name : Wencon Exhaust Compound  
Revision date : 14.03.2021  
Print date : 14-03-2021

Version (Revision) : 4.0.0 (3.0.0)

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

### 1.1 Product identifier

Wencon Exhaust Compound (WENCON EXHAUST COMP)  
PR-number (Danish): 1442098

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

High temperature steel repair paste

#### Relevant identified uses

In compliance with the conditions described in the annex to this safety data sheet. See section 16 for a comprehensive list of uses, for which an exposure scenario is provided as an annex.

#### Sectors of use [SU]

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

#### Process categories [PROC]

PROC 19 - Manual activities involving hand contact

PROC 21 - Low energy manipulation of substances bound in materials and/or articles

PROC 24 - High (mechanical) energy work-up of substances bound in/on materials and/or articles

#### Environmental release categories [ERC]

ERC 8c - Widespread use leading to inclusion into/onto article (indoor)

ERC 8f - Widespread use leading to inclusion into/onto article (outdoor)

ERC 10a - Widespread use of articles with low release (outdoor)

ERC 11a - Widespread use of articles with low release (indoor)

#### Article categories [AC]

AC 7 - Metal articles

#### Uses advised against

Do not use for private purposes (household).

#### Remark

The product is intended for professional use.

### 1.3 Details of the supplier of the safety data sheet

Supplier (manufacturer) : Wencon ApS  
Street : Jyllandsvej 15  
Postal code/city : DK-5400 BOGENSE  
Telephone : +45 6481 1010  
Information contact : wencon@wencon.com

### 1.4 Emergency telephone number

+44 870 600 62 66 (UK National Poisons Emergency Number)  
European emergency number: 112. Denmark: (Giftlinjen +45 82 12 12 12), only for the purpose of informing medical personnel in cases of acute intoxications.

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Carc. 2 ; H351 - Carcinogenicity : Category 2 ; Suspected of causing cancer.

### 2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms

Trade name : Wencon Exhaust Compound  
Revision date : 14.03.2021  
Print date : 14-03-2021

Version (Revision) : 4.0.0 (3.0.0)



Health hazard (GHS08)

**Signal word**

Warning

**Hazard components for labelling**

CARBON BLACK ; CAS No. : 1333-86-4

**Hazard statements**

H351 Suspected of causing cancer.

**Precautionary statements**

P202 Do not handle until all safety precautions have been read and understood.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P405 Store locked up.

**2.3 Other hazards**

None

**SECTION 3: Composition/information on ingredients**

**3.2 Mixtures**

**Hazardous ingredients**

SILICON ; EC No. : 231-130-8; CAS No. : 7440-21-3

Weight fraction :  $\geq 1 - < 2,5 \%$

Classification 1272/2008 [CLP] : Flam. Sol. 2 ; H228 Skin Irrit. 2 ; H315 Eye Irrit. 2 ; H319 STOT SE 3 ; H335

CARBON BLACK ; REACH No. : 01-2119384822-32 ; EC No. : 215-609-9; CAS No. : 1333-86-4

Weight fraction :  $\geq 1 - < 2,5 \%$

Classification 1272/2008 [CLP] : Carc. 2 ; H351

**Additional information**

Full text of H- and EUH-phrases: see section 16.

**SECTION 4: First aid measures**

**4.1 Description of first aid measures**

**General information**

When in doubt or if symptoms are observed, get medical advice. Never give anything by mouth to an unconscious person or a person with cramps. In case of allergic symptoms, especially in the breathing area, seek medical advice immediately. If unconscious place in recovery position and seek medical advice.

**Following inhalation**

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

**In case of skin contact**

In case of skin reactions, consult a physician. Immediately remove any contaminated clothing, shoes or stockings. After contact with skin, wash immediately with plenty of water and soap. Do not use force or solvents to remove product incrustations from affected skin areas. Do not let product dry on skin.

**After eye contact**

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

**After ingestion**

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain

Trade name : Wencon Exhaust Compound  
Revision date : 14.03.2021  
Print date : 14-03-2021

Version (Revision) : 4.0.0 (3.0.0)

immediate medical attention. Do NOT induce vomiting. Keep at rest.

**Self-protection of the first aider**

First aider: Pay attention to self-protection!

**4.2 Most important symptoms and effects, both acute and delayed**

No information available.

**4.3 Indication of any immediate medical attention and special treatment needed**

None

**SECTION 5: Firefighting measures**

**5.1 Extinguishing media**

**Suitable extinguishing media**

alcohol resistant foam

**Unsuitable extinguishing media**

Water spray jet

**5.2 Special hazards arising from the substance or mixture**

Burning produces heavy smoke. Use suitable breathing apparatus.

**Hazardous combustion products**

Carbon monoxide

**5.3 Advice for firefighters**

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

**Special protective equipment for firefighters**

Wear a self-contained breathing apparatus and chemical protective clothing.

**5.4 Additional information**

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

**SECTION 6: Accidental release measures**

**6.1 Personal precautions, protective equipment and emergency procedures**

**For non-emergency personnel**

Do not breathe gas/fumes/vapour/spray. Remove all sources of ignition. Provide adequate ventilation. Remove persons to safety. Use personal protection equipment. See protective measures under point 7 and 8.

**For emergency responders**

Do not breathe gas/fumes/vapour/spray. Use personal protection equipment. See protective measures under point 7 and 8.

**6.2 Environmental precautions**

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Ensure waste is collected and contained.

**6.3 Methods and material for containment and cleaning up**

**For containment**

Ensure waste is collected and contained.

**For cleaning up**

Clean contaminated articles and floor according to the environmental legislation. Clean with detergents. Avoid solvent cleaners. Treat the recovered material as prescribed in the section on waste disposal.

**6.4 Reference to other sections**

None

**SECTION 7: Handling and storage**

Trade name : Wencon Exhaust Compound  
Revision date : 14.03.2021  
Print date : 14-03-2021

Version (Revision) : 4.0.0 (3.0.0)



## 7.1 Precautions for safe handling

### Protective measures

It is recommended to design all work processes always so that the following is excluded: Inhalation of vapours or spray/mists Skin contact Eye contact Do not breathe gas/fumes/vapour/spray. When using do not eat, drink, smoke, sniff. Wear personal protection equipment (refer to section 8). Never use pressure to empty container. Use only in well-ventilated areas.

### Measures to prevent fire

Keep away from sources of ignition - No smoking.

### Environmental precautions

Do not allow to enter into surface water or drains.

## 7.2 Conditions for safe storage, including any incompatibilities

### Requirements for storage rooms and vessels

Only use containers specifically approved for the substance/product. Keep/Store only in original container. Keep container tightly closed.

### Hints on joint storage

Keep away from:

### Further information on storage conditions

Keep only in the original container in a cool, well-ventilated place. Store in a place accessible by authorized persons only. Handle and open container with care.

## 7.3 Specific end use(s)

Observe instructions for use. The regulations of the national employment safety and employment protection commission about the handling for polyurethane/epoxy have to be observed.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

None

### 8.2 Exposure controls

#### Personal protection equipment



#### Eye/face protection

##### Suitable eye protection

Eye glasses with side protection

#### Skin protection

##### Hand protection

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. Wear cotton undermitten if possible.

**Suitable gloves type** : Disposable gloves.

**Suitable material** : NBR (Nitrile rubber)

**Required properties** : liquid-tight.

**Breakthrough time (maximum wearing time)** : > 60 minutes

**Thickness of the glove material** : > 0.5 mm

**Recommended glove articles** : EN 374

Trade name : Wencon Exhaust Compound  
Revision date : 14.03.2021  
Print date : 14-03-2021

Version (Revision) : 4.0.0 (3.0.0)

**Additional hand protection measures :** Do not wear gloves near rotary machines and tools. Check leak tightness/impermeability prior to use. Wear cotton undermitten if possible. Use gloves only once. Take recovery periods for skin regeneration.

**Remark :** For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. Observe the wear time limits as specified by the manufacturer. Breakthrough times and swelling properties of the material must be taken into consideration. In the case of wanting to use the gloves again, clean them before taking off and air them well. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. Barrier creams are not substitutes for body protection.

#### Body protection

**Remark :** Body protection: not required.

#### Respiratory protection

exceeding exposure limit values

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

##### Suitable respiratory protection apparatus

Combination filtering device (EN 14387) Filtering device (DIN EN 147) Full-/half-/quarter-face masks (DIN EN 136/140) Filtering Half-face mask (DIN EN 149) Particle filter device (DIN EN 143).

Filtering device (full mask or mouthpiece) with filter: A P

##### Additional measures for respiratory protection

Filter types: A, B, E, K. Class 1: Maximum permitted contaminant concentration in inhaled air = 1000 mL/m<sup>3</sup> (0.1 % by vol.); class 2: maximum permitted contaminant concentration in inhaled air = 5000 mL/m<sup>3</sup> (0.5 % by vol.); class 3: maximum permitted contaminant concentration in inhaled air = 10000 mL/m<sup>3</sup> (1.0 % by vol.) Half-face mask or quarter facepiece: maximum use concentration for substances with exposure limits: P1 filter: up to a max. of 4 times the exposure limit. P2 filter: up to a max. of 10 times the exposure limit. P3 filter: up to a max. of 30 times the expo. Full-face mask or mouthpiece with particulate filter: maximum use concentration for substances with exposure limits: P1 filter: up to a max. of 4 times the exposure limit. P2 filter: up to a max. of 15 times the exposure limit. P3 filter: up to a max. of

##### Remark

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

#### General information

When using do not eat, drink, smoke, sniff. Avoid contact with skin, eyes and clothes. Wash hands before breaks and after work. Immediately remove any contaminated clothing, shoes or stockings.

#### Other protection measures

##### Product related measures to prevent exposure

Further information: see technical data sheet.

##### Instructional measures to prevent exposure

Further information: see technical data sheet.

##### Organisational measures to prevent exposure

Further information: see technical data sheet.

##### Technical measures to prevent exposure

Technical measures and the application of suitable work processes have priority over personal protection equipment. See section 7. No additional measures necessary.

#### Environmental exposure controls

Do not allow to enter into surface water or drains.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance : Paste

Odour : characteristic

Trade name : Wencon Exhaust Compound  
Revision date : 14.03.2021  
Print date : 14-03-2021

Version (Revision) : 4.0.0 (3.0.0)

## Appearance

Colour : black

## Safety characteristics

Melting point/freezing point :		not applicable	
Initial boiling point and boiling range :	( 1013 hPa )	100 - 102 °C	
Decomposition temperature :		No data available	
Flash point :	>	100 °C	DIN 53213-1
Auto-ignition temperature :		No data available	
Evaporation rate :	<	1	
Flammable gases :		Not applicable.	
Flammable solids :		Not applicable.	
Oxidising properties.		No data available.	
Lower explosion limit :		No data available	
Upper explosion limit :		No data available	
Explosive properties :		No data available.	
Vapour pressure :	( 50 °C )	<	1000 hPa
Relative vapour density :		No data available	
Relative density :	( 20 °C )		1,3 g/cm <sup>3</sup> DIN 53217
Water solubility :	( 20 °C )		practically insoluble
Partition coefficient n-octanol/water :		No data available	
pH :		No data available	
Viscosity :	( 20 °C )		not applicable
Cinematic viscosity :	( 40 °C )		No data available
Odour threshold :		No data available	

## 9.2 Other information

None

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No information available.

### 10.2 Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

### 10.3 Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

### 10.4 Conditions to avoid

Ignition hazard.

### 10.5 Incompatible materials

No information available.

### 10.6 Hazardous decomposition products

Does not decompose when used for intended uses.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

#### Respiratory or skin sensitisation

Harmful: possible risk of irreversible effects through inhalation, in contact with skin and if swallowed. Risk of serious damage to eyes. Harmful: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed.

#### CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Trade name : Wencon Exhaust Compound  
Revision date : 14.03.2021  
Print date : 14-03-2021

Version (Revision) : 4.0.0 (3.0.0)

**Carcinogenicity**  
**Assessment/classification**  
Suspected of causing cancer. Carc. 2, H351

## SECTION 12: Ecological information

### 12.1 Toxicity

There are no data available on the mixture itself.

#### **Aquatic toxicity**

The substance/mixture does not fulfill the criteria of the acute aquatic toxicity according to Regulation (EC) No 1272/2008 [CLP], Annex I.

#### **Sediment toxicity**

**Toxicity to soil macroorganisms**  
**Acute earthworm toxicity**  
**Chronical earthworm toxicity (reproduction)**  
**Long-term toxicity of organisms living in the sediment**

### 12.2 Persistence and degradability

No information available.

### 12.3 Bioaccumulative potential

No information available.

### 12.4 Mobility in soil

No information available.

### 12.5 Results of PBT and vPvB assessment

No information available.

### 12.6 Other adverse effects

No information available.

### 12.7 Additional ecotoxicological information

The ecotoxicological properties of this mixture are determined by the ecotoxicological properties of the single components (see section 3). Do not allow to enter into surface water or drains.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### **Product/Packaging disposal**

Do not allow to enter into surface water or drains.

#### **Waste treatment options**

##### **Appropriate disposal / Product**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste. Dispose of waste according to applicable legislation.

##### **Appropriate disposal / Package**

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Packing which cannot be properly cleaned must be disposed of. Handle contaminated packages in the same way as the substance itself.

## SECTION 14: Transport information

### 14.1 UN number

No dangerous good in sense of these transport regulations.

### 14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

Trade name : Wencon Exhaust Compound  
Revision date : 14.03.2021  
Print date : 14-03-2021

Version (Revision) : 4.0.0 (3.0.0)

#### 14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

#### 14.4 Packing group

No dangerous good in sense of these transport regulations.

#### 14.5 Environmental hazards

No dangerous good in sense of these transport regulations.

#### 14.6 Special precautions for user

None

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU legislation

##### Authorisations and/or restrictions on use

##### Restrictions on use

Use restriction according to REACH annex XVII, no. : 3, 40

##### National regulations

REACH-Regulation(1907/2006) Annex XVII [RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES] 3

**MAL code number according to Executive Order no. 301 from 13 May 1993 on the determination of code numbers (The Danish Working Environment Service)**

MAL code number 00-4

#### 15.2 Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

### SECTION 16: Other information

#### 16.1 Indication of changes

02. Classification of the substance or mixture · 02. Label elements · 02. Labelling according to Regulation (EC) No. 1272/2008 [CLP] · 02. Labelling according to Regulation (EC) No. 1272/2008 [CLP] - Hazard components for labelling · 03. Hazardous ingredients · 04. Effects · 11. Skin corrosion/irritation · 11. Serious eye damage/eye irritation · 11. Carcinogenicity - Assessment/classification · 11. STOT-single exposure - STOT SE 1 and 2 · 12. Aquatic toxicity · 15. Restrictions on use

#### 16.2 Abbreviations and acronyms

ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road  
ASTM = American Society of Testing and Materials (US)  
CAS No = Chemical Abstracts Service Number (see ACS - American Chemical Society)  
DNEL = Derived No-Effect Level  
DT50 = Time for 50% loss; half-life  
EbC50 = Median effective concentration (biomass, e.g. of algae)  
EC50 = Median effective concentration  
EINECS = European Inventory of Existing Commercial Chemical Substances  
ELINCS = European List of Notified (New) Chemicals (see Tab 7, Background - Guide)  
ErC50 = Median effective concentration (growth rate, e.g. of algae)  
EWC = European Waste Catalogue  
IATA = International Air Transport Association  
IC50 = Concentration that produces 50% inhibition  
IMDG = International Maritime Dangerous Goods Code  
IMO = International Maritime Organization  
LC50 = Concentration required to kill 50% of test organisms  
LD50 = Dose required to kill 50% of test organisms  
LEL = Lower Explosive Limit/Lower Explosion Limit



Trade name : Wencon Exhaust Compound  
Revision date : 14.03.2021  
Print date : 14-03-2021

Version (Revision) : 4.0.0 (3.0.0)

---

LOAEL = Lowest observed adverse effect level  
MRL = Maximum Residue Limit  
NOAEL = No Observed Adverse Effect Level  
NOEC = No observed effect concentration  
NOEL = No Observable Effect Level  
OEL = Occupational Exposure Limits  
PBT = Persistent, Bioaccumulative or Toxic  
PNEC = Previsible Non Effect Concentration  
STEL = Short-Term Exposure Limit  
TWA = Time-Weighted Average  
vPvB = Very Persistent and Very Bioaccumulative

### 16.3 Key literature references and sources for data

None

### 16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

No information available.

### 16.5 Relevant H- and EUH-phrases (Number and full text)

H228	Flammable solid.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.

### 16.6 Training advice

The regulations of the national employment safety and employment protection commission about the handling for polyurethane/epoxy have to be observed.

### 16.7 Additional information

This safety data sheet contains more than one ES in an integrated form. Contents of the exposure scenarios have been included into sections 1.2, 8, 9, 12, 15 and 16 of this safety data sheet.

---

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

---